

### ADA Ductile iron longitudinal grating


**Product Features:**

- Certified to EN 1433 Load Class D 400 kN - 89,920 lbs.
- Uses fiX self-locking system.
- Suitable to use with NW150 channels.
- Manufactured from ductile iron.
- Complies with ADA - American Disabilities Act.

**Installation:**

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

**Gratings FILCOTEN® pro – v 150 (6") with fiX self-locking system.**

	Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight Lbs Kg		Inlet cross-section sq.inches	Inlet cross-section cm2/m
○	17015104	ADA ductile iron longitudinal grating	ductile iron	19.70"/6.77"/0.78" 500/172/20	D 400 kN	Mesh 1.14" by 0.51" (MW29x13 mm)	11.46	5.2	110.05	710

**Specification:** FILCOTEN pro-tec NW150, extra heavy duty, (Load Class D 400 kN), ductile iron, reinforced grate is 6.77" (172mm) wide, 19.70" (500mm) long, 0.78" (20mm) high, weighing 11.46 lbs (5.2 kg). The grate has 0.51" (13mm) wide, 1.14" (29mm) long mesh and is ADA compliant and Class D load rated - for pneumatic forklift traffic, roads and highways. The grate is secured to the body with four point fiX self-locking (snap-on) system. Galvanized steel manufactured and tested according to EN1433 - CE certified.

D400kN MW29/13: GJS 17015104

