


ADA Mesh grating - Galvanized steel


Product Features:

- Certified to EN 1433 Load Class D 400 kN - 89,920 lbs.
- Uses fiX self-locking system.
- Suitable to use with NW150 channels.
- Manufactured from galvanized steel
- Hot-Dip galvanized material.
- Complies with ADA - American Disabilities Act.

Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Gratings FILCOTEN® pro – v 150 (6") with fiX self-locking system.

	Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight		Inlet cross-section sq.inches	Inlet cross-section cm2/m
							Lbs	Kg		
○	17015226	ADA Mesh grating	galvanized steel	39.40"/6.77"/0.78" 1000/172/20	D 400 kN	MW 0.98" x 0.39" (MW25x10mm)	22.93	10.4	167.4	1,080
○	17015227	ADA Mesh grating	galvanized steel	19.70"/6.77"/0.78" 500/172/20	D 400 kN	MW 0.98" x 0.39" (MW25x10mm)	11.68	5.3	166.63	1,075

Specification: FILCOTEN pro-tec NW150, extra heavy duty, (Load Class D 400 kN), galvanized steel, reinforced grate is 6.77" (172mm) wide, 39.40" (1000mm) long, 0.78" (20mm) high, weighing 22.93 lbs (10.4 kg). The grate has 0.39" (10mm) wide, 0.98" (25mm) long slots and is ADA compliant and Class B load rated - for pneumatic forklift traffic, roads and highways. The grate is secured to the body with four point fiX self-locking (snap-on) system. Galvanized steel manufactured and tested according to EN1433 - CE certified.

D400kN MW25/10: V 17015226 (17015227)

