

ADA HEELPROOF COMBee grating

Product Features:

- Certified to EN 1433 Load Class C 250 kN 56,200 lbs.
- Uses fiX self-locking system.
- Suitable to use with NW100 channels.
- Manufactured from composite plastic.
- With antislip surface structure.
- Complies with ADA - American Disabilities Act.

Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Gratings FILCOTEN® tec – 100 (4") with fiX self-locking system.

| | Item no. | Gratings | Material | Dimention | Load class as per EN- standard | Slot-/Mesh width | Weight | | Inlet cross- section sq.inches | Inlet cross- section cm2/m |
|---|----------|---------------------------------|-----------|----------------------------------|--------------------------------------|-----------------------|--------|-----|--------------------------------------|----------------------------------|
| | | | | | | | Lbs | Kg | | |
| ○ | 17010402 | ADA HEELPROOF COMBee grating | Polyamide | 19.40"/4.84"/0.78" 500/123/20 | C 250 kN | Ø 0.31" hole (8.0 mm) | 2.43 | 1.1 | 44.95 | 290 |

Specification: FILCOTEN pro-tec NW100, heavy duty, (Load Class C 250 kN), composite plastic, reinforced grate is 4.84" (123mm) wide, 19.70" (500mm) long, 0.78" (20mm) high, weighing 2.43 lbs (1.1 kg). The grate has Ø 0.31" (8.0mm) diameter hole and is ADA compliant and Class C load rated - commercial applications. The grate is secured to the body with four point fiX self-locking (snap-on) system. Composite plastic manufactured and tested according to EN1433 - CE certified.

C250kN Ø7,3: PA 17010402

