

### ADA HEELPROOF COMBee grating



#### Product Features:

- Certified to EN 1433 Load Class B 125 kN 28,100 lbs per foot.
- Uses fiX self-locking system.
- Suitable to use with NW100 channels.
- Manufactured from composite plastic.
- With antislip surface structure.
- Complies with ADA - American Disabilities Act.

#### Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

#### Gratings FILCOTEN® pro – tec 100 (4") with fiX self-locking system.

	Item no.	Gratings	Material	Dimention	Load class as per EN- standard	Slot-/Mesh width	Weight		Inlet cross- section sq.inches/m	Inlet cross- section cm2/m
							Lbs	Kg		
○	17010401	ADA HEELPROOF COMBee grating	Polyamide	19.40"/4.84"/0.78" 500/123/20	B 125 kN	Ø 0.28" hole (7.2 mm)	2.43	1.1	44.95	290

**Specification:** FILCOTEN pro-tec NW100, medium duty, (Load Class B 125 kN), composite plastic, reinforced grate is 4.84" (123mm) wide, 19.70" (500mm) long, 0.78" (20mm) high, weighing 2.43 lbs (1.1 kg). The grate has Ø 0.28" (7.2mm) diameter hole and is ADA compliant and Class B load rated - light pneumatic tire traffic, sidewalks and residential parking. The grate is secured to the body with four point fiX self-locking (snap-on) system. Composite plastic manufactured and tested according to EN1433 - CE certified.

B125kN Ø7,2: PA 17010401

