

**HEELPROOF Ductile iron grating "VILLE"**



**Product Features:**

- Certified to EN 1433
- Load Class E 600 kN (134,800 lbs per foot)
- Uses fiX self-locking system
- Two anti-vandalism devices per grate can be installed to prevent theft
- Suitable to use with NW200 channels
- Manufactured from ductile iron
- Heelproof
- Complies with ADA - American Disabilities Act.

**Installation:**

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations

Gratings FILCOTEN® pro 200 (8") with fiX self-locking system.

Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight		Inlet cross-section	Inlet cross-section
						Lbs	Kg	sq.inches/m	cm2/m
○ 17020180	HEELPROOF Ductile iron grating "VILLE"	ductile iron	19.70"/8.74"/0.78" 500/222/20	E 600 kN	0.31" wide slots (SW 8mm)	23.59	10.7	45.9	296

**Specification:** FILCOTEN pro-G NW200, extra heavy duty, (Load Class E 600 kN), ductile iron, reinforced grate is 8.74" (222mm) wide, 19.70" (500mm) long, 0.78" (20mm) high, weighing 23.59 lbs (10.7 kg). The grate has 0.31" (8mm) wide slots and is Class E load rated - for commercial solid tire traffic patterns, and impacts from steel struts or metal wheels (forklifts). The grate is secured to the body with four point fiX self-locking (snap-on) system. To prevent theft of grate, two anti-vandalism device per grate can be installed. Ductile iron manufactured and tested according to EN1433 - CE certified.

E600kN SW8mm: GJS 17020180,

