


# Environmental data sheet:

## BG-FILCOTEN® one

### Drainage channels made of FILCOTEN® HPC (High Performance Concrete)

- Verified LCA (life cycle analysis) according to ISO 14040 respectively EN15804
- Certified energy – and environmental management system ISO 50001 and ISO 14001 at the place of production in Oberwang/Upper Austria
- Quality class UA according to the guidelines for recycling of building materials (Building Materials Recycling Association AT)
- IBR certified – biologically tested for – VOC, biocides, radioactivity

Technical data: <b>BG-FILCOTEN® one</b>	<b>150 - 0</b>	<b>150 40-0</b>	<b>200 - 0</b>	<b>200 40-0</b>
Dimensions [mm] L/W/H	1000/210/300	1000/210/500	1000/260/335	1000/260/535
Capacity [l/m]	22	52	37	77
Discharge cross-section [cm <sup>2</sup> ]	220	520	370	770

Weight [kg] one	76.6	107.5	106.0	136.5
Global Warming Potential [kgCO <sub>2</sub> -eq] 	<b>21.3</b>	<b>29.8</b>	<b>29.4</b>	<b>37.9</b>

### Environmental indicators:

Value basis LCA environmental indicators according to ISO 14040 and ISO 14044 modules A1-A4 (A4: 200 km truck transport standardly assumed) in accordance with EN 15804, BG-Graspointner 2017, provided by ECODESIGN company - [www.ecodesign-company.com](http://www.ecodesign-company.com) and verified by ESU-services GmbH, Schaffhausen, Switzerland - [www.esu-services.ch](http://www.esu-services.ch)

BG-FILCOTEN® pro is a product family of BG-Graspointner GmbH | [www.bg-graspointner.com](http://www.bg-graspointner.com)

