

HEELPROOF Ductile iron grating "VILLE"



Product Features:

- Certified as per European standard EN 1433
- Load Class E 600 kN (134,800 lbs per foot)
- Uses fiX self-locking system
- Suitable to use with NW150 channels
- Manufactured from ductile iron
- Heelproof
- Complies with ADA - American Disabilities Act.
- Suitable to use with Anti-vandalism device to prevent theft.

Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Gratings FILCOTEN® pro 150 (6") with fiX self-locking system.

	Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight		Inlet cross-section sq.inches/m	Inlet cross-section cm2/m
							Lbs	Kg		
○	17015180	HEELPROOF grating "VILLE"	ductile iron	19.70"/6.77"/0.78" 500/172/20	E 600 kN	0.31" wide slots (SW 8mm)	18.96	8.6	26.4	170

Specification: FILCOTEN pro-tec NW150, extra heavy duty, (Load Class E 600 kN), ductile iron, reinforced grate is 6.77" (172mm) wide, 19.70" (500mm) long, 0.78" (20mm) high, weighing 18.96 lbs (8.6 kg). The grate has 0.31" (8mm) wide slots and is Class E load rated - for commercial solid tire traffic patterns, and impacts from steel struts or metal wheels (forklifts). The grate is secured to the body with four point fiX self-locking (snap-on) system. To prevent theft of grate, two anti-vandalism device per grate can be installed. Ductile iron manufactured and tested according to EN1433 - CE certified.

E600kN SW8mm: GJS 17015180

