


### ADA Mesh grating - Galvanized steel



#### Product Features:

- Certified as per European standard EN 1433
- Load Class B 125 kN 28,100 lbs.
- Uses fiX self-locking system.
- Suitable to use with NW100 channels.
- Manufactured from galvanized steel
- Hot-Dip galvanized material.
- Complies with ADA - American Disabilities Act.
- Suitable to use with Anti-vandalism device to prevent theft.

#### Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Gratings FILCOTEN® pro-tec – v 100 (4") with fiX self-locking system.

	Item no.	Gratings	Material	Dimension	Load class as per EN-standard	Slot-/Mesh width	Weight		Inlet cross-section sq.inches/m	Inlet cross-section cm <sup>2</sup> /m
							Lbs	Kg		
○	17010220	ADA Mesh grating	galvanized steel	39.40"/4.80"/0.78" 1000/122/20	B 125 kN	MW1.18" x 0.39" (MW30x10mm)	6.17	2.8	151.9	980
○	17010221	ADA Mesh grating	galvanized steel	19.70"/4.80"/0.78" 500/122/20	B 125 kN	MW1.18" x 0.39" (MW30x10mm)	3.09	1.4	147.25	950

**Specification:** FILCOTEN pro-tec NW100, medium duty, (Load Class B 125 kN), galvanized steel, reinforced grate is 4.80" (122mm) wide, 39.40" (1000mm) long, 0.78" (20mm) high, weighing 6.17 lbs (2.8 kg). The grate has 0.39" (10mm) wide, 1.18" (30mm) long slots and is ADA compliant and Class B load rated - light pneumatic tire traffic, sidewalks and residential parking. The grate is secured to the body with four point fiX self-locking (snap-on) system. Galvanized steel manufactured and tested according to EN1433 - CE certified.

B125kN MW30/10: V 17010220 (17010221)

