

HEELPROOF Ductile iron grating "KIARO"



Product Features:

- Certified to EN 1433
- Load Class D 400 kN (89,920 lbs per foot)
- Uses fiX self-locking system
- Suitable to use with NW200 channels
- Manufactured from ductile iron
- Heelproof
- Complies with ADA - American Disabilities Act.

Installation:

- The trench drain system and grates shall be installed in accordance with the manufacturer's installation instructions and recommendations.

Gratings FILCOTEN® pro 200 (8") with fiX self-locking system.

	Item no.	Gratings	Material	Dimention	Load class as per EN- standard	Slot-/Mesh width	Weight		Inlet cross-section sq.inches/m	Inlet cross- section cm2/m
							Lbs	Kg		
○	17020183	HEELPROOF Ductile iron grating "KIARO"	ductile iron	19.70"/8.74"/0.78" 500/222/20	D 400 kN	SW 7.87" x 0.22" (SW200x5.7mm)	20.72	9.4	106	684

Specification: FILCOTEN pro NW200, extra heavy duty, Load Class D 400 kN, ductile iron, reinforced grate is 8.74" (222mm) wide, 19.70" (500mm) long, 0.78" (20mm) high, weighing 20.72lbs (9.4 kg). The grate has 0.22" (5.7mm) wide slots and is ADA compliant, Heelproof and Class D load rated - for pneumatic forklift traffic, roads and highways. The grate is secured to the body with four point fiX self-locking (snap-on) system. Ductile iron manufactured and tested according to EN1433 - CE certified.

D400kN SW5.7mm: GJS 17020183

